

**DA BOMB 2014 FRAME GEOMETRY CHART**

モデル	サイズ	水平トップ	シート長	チェーンステー	ヘッド角	シート角	BB高さ	ホイールベース	推奨フォーク	ヘッド規格	BB幅	ISCG	リア幅	シートポスト	Shock	Reach	Stack
EXPLOSIVE	26*16"	592mm	406mm	435/445	63.5°	62.5°	351mm	1199mm	180-200mm	ZS44/ZS56	83mm	05	150*12mm	30.9mm	240*76		
DYNAMITE 275	27.5*16"	580mm	406mm	438mm	67°	68°	337mm	1155mm	140-160mm	ZS44/ZS56	73mm	05	142*12mm	30.9mm	215*63		
EMP Attack	26*16"	570mm	406mm	435mm	68°	71°	342mm	1134mm	120-160mm	ZS44/ZS56	68mm	05	142*12mm	30.9mm	190*50		
Revolution	26*13.5"	575mm	343mm	420mm	69°	70°	327mm	1082mm	100-120mm	ZS44/ZS56	73mm	05	142*12mm	30.9mm	165*38		
Warhawk	26*14"	559mm	356mm	410mm	70°	73°	322mm	1035mm	80-100mm	ZS44/ZS55	73mm	05	135mm QR	30.9mm	-		
Carbon KARMA 26"	26*15.5"	555mm	394mm	425mm	70°	73°	308mm	1040mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		
	26*17.5"	591mm	445mm		70°	73°		1076mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		
	26*19.5"	625mm	495mm		70°	73°		1111mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		
Carbon KARMA 27.5"	27.5*16"	555mm	406mm	425mm	70°	73.5°	301mm	1057mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		
	27.5*18"	575mm	457mm		70.5°	73°	313mm	1054mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		
	27.5*20"	596mm	508mm		70.8°	72.7°	313mm	1069mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		
Carbon KARMA 29"	29*16"	571mm	406mm	450mm	70.7°	73.7°	302mm	1076mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		
	29*18"	594mm	457mm		71°	73.5°		1089mm	80-100mm	IS42/IS52	68mm	-	135mm QR	31.6mm	-		

**FIREEYE 2014 FRAME GEOMETRY CHART**

モデル	サイズ	水平トップ	シート長	チェーンステー	ヘッド角	シート角	BB高さ	ホイールベース	推奨フォーク	ヘッド規格	BB幅	ISCG	リア幅	シートポスト	Shock	Reach	Stack
Burning 650B専用	XS	560mm	368mm	444.4mm	67.5°	73.5°	+9mm	1117.9mm	150mm	上1-1/8" 下1.5"(56)	73mm	05	142*12mm	31.6mm	7.875"*2. 25" 22mm*M	384mm	593mm
	SM	575mm	406mm					1133.4mm								398.5mm	598mm
	MD	600mm	457mm					1158.9mm								424.5mm	603mm
Hot Tail26 ( )=650B	S, 16.5"	570mm	419.1mm	420mm	67°	72°	303.3mm (322.35mm)	1064mm	150-160mm A to C = 540mm	上44/下44	73mm	05	135mm QR	31.6mm	-		
	M, 17.5"	590mm	444.5mm					1084mm									
	L, 19"	610mm	482.6mm					1104mm									
Flame ( )=650B	S, 16.5"	570mm	419.1mm	420mm	68°	72°	310.3mm (329mm)	1053mm	120-150mm A to C = 519mm	IS42/IS52	73mm	05	135mm QR	31.6mm	-		
	M, 17.5"	590mm	444.5mm					1073mm									
	L, 19"	610mm	482.6mm					1093mm									
Funseeker ( )=650B	S, 16.5"	570mm	419.1mm	420mm	69.5°	72.5°	311.3mm (330mm)	1034mm	120-140mm A to C = 490mm	上44/下44	68mm	-	135mm QR	27.2mm	-		
	M, 17.5"	590mm	444.5mm					1054mm									
	L, 19"	610mm	482.6mm					1074mm									
Shorftfuse	13"	573mm	315mm	380-395	69°	71°	305.2mm	1008mm	100mm A to C = 475mm	fully integrated	68mm	-	135*10mm	27.2mm	-		
Hot Tail29	S, 16.5"	563mm	419.1mm	420mm	68°	73.5°	315.3mm	1068mm	130-140mm A to C = 540mm	上44/下44	73mm	05	135mm QR	31.6mm	-		
	M, 17.5"	583mm	444.5mm					1088mm									
	L, 19"	603mm	482.6mm					1108mm									

### BTR Fabricatios FRAME GEOMETRY CHART

モデル	サイズ	水平トップ	シート長	チェーンステー	ヘッド角	シート角	BB高さ	ホイールベース	推奨フォーク	ヘッド規格	BB幅	ISCG	リア幅	シートポスト	Shock	Reach	Stack
Belter	S	604mm	360mm	415mm	61°	72°	-47mm =283mm	1183mm	150-160mm A to C = 545mm	上44/下44	83mm	05	150*12mm	27.2mm	-	400mm	628.5m
	M	624mm	375mm					1203mm								420mm	628.5m
	L	644mm	390mm					1223mm								440mm	628.5m
Ranger	S	560mm	400mm	415mm	64°	75°	-40mm =290mm	1134mm	120mm A to C = 500mm	上44/下44	73mm	05	135*12mm	30.9mm	-	400mm	598.6m
	M	580mm	420mm					1154mm								420mm	
	L	600mm	445mm					1174mm								440mm	
Ripper	Short	501.6mm	304mm	370mm	62°	72°	-30mm =275mm	1009.1mm	100mm A to C = 473mm	上44/下44	73mm	05	135mm QR	27.2mm	-	330mm	528.2m
	Long	521.6mm	304mm					1029.1mm								350mm	

### MOREWOOD 2014 FRAME GEOMETRY CHART

モデル	サイズ	水平トップ	シート長	チェーンステー	ヘッド角	シート角	BB高さ	ホイールベース	推奨フォーク	ヘッド規格	BB幅	ISCG	リア幅	シートポスト	Shock	Reach	Stack
MAKULU	S	580mm	414mm	438mm	64°	65°	352mm (+22mm)	1158mm	Axle to Crown 565mm	上44/下50	83mm	05	150*12mm	30.9mm	10.5"*3.5 " 267*89m	380mm	581mm
	M	605mm						1183mm								405mm	
	L	635mm						1213mm								435mm	
MAKULU 275	S																
	M																
	L																
KALULA	S	550mm	414mm	438mm	65.5°	67.3°	352mm (+22mm)	1109mm	Axle to Crown 565mm	上44/下50	83mm	05	150*12mm	30.9mm	9.5"*3" 241*76m m	347mm	590mm
	M	580mm						1139mm								377mm	
	L	610mm						1169mm								407mm	
IZIMU	S	565mm	390mm	442mm	65.5°	67.3°	360mm (+30mm)	1138mm	Axle to Crown 565mm	上44/下50	73mm	05	150*12mm	30.9mm	9.5"*3" 241*76m m	366mm	579mm
	M	595mm	400mm					1168mm								396mm	
	L	625mm	410mm					1198mm								426mm	
SUKUMA	S	560mm	405mm	428mm	67.5°	72.5° (70)	335mm (+5mm)	1090mm	528mm* 40mm+4.0	上44/下50	92mm	05	142*12mm	30.9mm	7.875"*2. 25" 200*57m	379mm	573mm
	M	585mm	460mm					1116mm								401mm	
	L	610mm	500mm					1141mm								426mm	
JABULA	S	560mm	405mm	433mm	66.5°	72.5° (70)	340mm (+10mm)	1113mm	555mm* 40mm+4.0	上44/下50	92mm	05	142*12mm	30.9mm	8.5"*2.25 " 216*63m	379mm	573mm
	M	585mm	460mm					1139mm								401mm	
	L	610mm	500mm					1164mm								426mm	
ZULA 275	S																
	M																
	L																
KWELA29	S	580mm	400mm	440mm	71°	72°	676.6mm (-60mm)	1067mm	486mm	上44/下50	73mm	-	135mm QR	30.9mm	-	395mm	604mm
	M	605mm	450mm					1093mm								417mm	
	L	630mm	500mm					1118mm								439mm	