

## The Following

<b>120mm fork</b>				
GEOMETRY	SMALL	MEDIUM	LARGE	X-LARGE
A - Head Tube Angle LOW	67.9°	67.9°	67.9°	67.9°
Head Tube Angle X-LOW	67.2°	67.2°	67.2°	67.2°
B - Seat Tube Angle LOW	77°	77°	77°	77°
Seat Tube Angle X-LOW	76.5°	76.5°	76.5°	76.5°
C - Virtual Top Tube Length	585mm   23.03"	609mm   23.98"	626mm   24.63"	646mm   25.45"
D - Seat Tube Length	381mm   15.00"	432mm   17.00"	470mm   18.50"	508mm   20.00"
E - Bottom Bracket Height LOW	335mm   13.17"	335mm   13.17"	335mm   13.17"	335mm   13.17"
Bottom Bracket Height X-LOW	327mm   12.86"	327mm   12.86"	327mm   12.86"	327mm   12.86"
F - Bottom Bracket Drop	36mm   1.40"	36mm   1.40"	36mm   1.40"	36mm   1.40"
G - Head Tube Length	90mm   3.54"	110mm   4.33"	110mm   4.33"	120mm   4.72"
H - Chain Stay Length LOW	430mm   16.93"	430mm   16.93"	430mm   16.93"	430mm   16.93"
Chain Stay Length X-LOW	432mm   17.01"	432mm   17.01"	432mm   17.01"	432mm   17.01"
I - Wheel Base LOW	1148mm   45.19"	1176mm   46.28"	1196mm   47.07"	1219mm   48.00"
Wheel Base X-LOW	1149mm   45.24"	1177mm   46.32"	1197mm   47.11"	1220mm   48.05"
J - Axle to Crown LOW	521mm   20.51"	521mm   20.51"	521mm   20.51"	521mm   20.51"
K - Offset	51mm   2.01"	51mm   2.01"	51mm   2.01"	51mm   2.01"
L - Front to Center	720mm   28.36"	748mm   29.44"	768mm   30.23"	792mm   31.16"
M - Trail LOW	96mm   3.76"	96mm   3.76"	96mm   3.76"	96mm   3.76"
Trail X-LOW	100mm   3.93"	100mm   3.93"	100mm   3.93"	100mm   3.93"
N - Stack	586mm   23.06"	604mm   23.79"	604mm   23.79"	614mm   24.15"
O - Reach	440mm   17.34"	460mm   18.12"	480mm   18.91"	500mm   19.70"
P - Standover	650mm   25.59"	664mm   26.15"	675mm   26.56"	689mm   27.12"

<b>130mm fork</b>				
GEOMETRY	SMALL	MEDIUM	LARGE	X-LARGE
A - Head Tube Angle LOW	66.9°	66.9°	66.9°	66.9°
Head Tube Angle X-LOW	66.4°	66.4°	66.4°	66.4°
B - Seat Tube Angle LOW	76.0°	76.0°	76.0°	76.0°
Seat Tube Angle X-LOW	75.5°	75.5°	75.5°	75.5°
C - Virtual Top Tube Length	584mm   22.99"	611mm   24.04"	631mm   24.83"	652mm   25.67"
D - Seat Tube Length	381mm   15.00"	432mm   17.00"	470mm   18.50"	508mm   20.00"
E - Bottom Bracket Height LOW	334mm   13.14"	337mm   13.28"	337mm   13.28"	337mm   13.28"
Bottom Bracket Height X-LOW	326mm   12.82"	329mm   12.96"	329mm   12.96"	329mm   12.96"
F - Bottom Bracket Drop	36mm   1.40"	36mm   1.40"	36mm   1.40"	36mm   1.40"
G - Head Tube Length	90mm   3.54"	110mm   4.33"	110mm   4.33"	120mm   4.72"
H - Chain Stay Length LOW	430mm   16.93"	430mm   16.93"	430mm   16.93"	430mm   16.93"
Chain Stay Length X-LOW	432mm   17.01"	432mm   17.01"	432mm   17.01"	432mm   17.01"
I - Wheel Base LOW	1156mm   45.50"	1183mm   46.58"	1203mm   47.37"	1227mm   48.31"
Wheel Base X-LOW	1157mm   45.55"	1185mm   46.64"	1205mm   47.43"	1228mm   48.36"
J - Axle to Crown	541mm   21.30"	541mm   21.30"	541mm   21.30"	541mm   21.30"
K - Offset	51mm   2.01"	51mm   2.01"	51mm   2.01"	51mm   2.01"
L - Front to Center	727mm   28.63"	755mm   29.71"	775mm   30.50"	799mm   31.44"
M - Trail LOW	100mm   3.94"	100mm   3.94"	100mm   3.94"	100mm   3.94"
Trail X-LOW	104mm   4.11"	104mm   4.11"	104mm   4.11"	104mm   4.11"
N - Stack	586mm   23.06"	604mm   23.79"	604mm   23.79"	614mm   24.15"
O - Reach	440mm   17.34"	460mm   18.13"	480mm   18.91"	500mm   19.70"
P - Standover	652mm   25.67"	666mm   26.22"	677mm   26.65"	690mm   27.17"